

SANWA CD800A

DIGITAL MULTITESTER



SPECIFICATION



CD800a	Measuring range	Best accuracy	Resolution	Input impedance
DCV	400m/4/40/400/600V	± (0.7%+3)	0.1mV	DCV: 10M~ 100MΩ
ACV	4/40/400/600V	± (1.6%+9)	0.001V	ACV: 10M~ 11MΩ
DCA	40m/400mA	± (2.2%+5)	0.01mA	
ACA	40m/400mA	± (2.8%+5)	0.01mA	
Resistance	400/4k/40k/400k/4M/40MΩ	± (1.5%+5)	0.1Ω	
Capacitance	50n/500n/5μ/50μ/100μF	± (5%+10)	0.01nF	
Frequency	5Hz~100kHz	± (0.5%+3)		
Duty cycle	20%~80%	± (0.5%+5)		
Continuity	Buzzer sounds at between 10Ω and 120Ω. Open voltage : approx. 0.4V			
Diode test	Open voltage : approx. 1.5V			

Bandwidth	40~400Hz		
Fuse / Battery	0.5A/250V 1.5kA φ5.2X20 ceramic	R6PX2	
Size / Mass	H176XW104XD46mm/approx. 340g		
Standard accessories included	Hand strap , [instruction manual]		